AQE Series 50mJ Diode Pumped Actively Q-switched Laser



The AQE series is a self-developed stack-pumped actively Q-switched laser by RealLight. Utilizing our proprietary miniature diode laser arrays for uniform pumping, it features an integrated design combining the laser-sealed cavity with the driving control circuit, enabling compact, high-peak-power actively Q-switched laser output. This product is widely used in fields such as radar, processing and scientific research.

Key Features

- Multiple wavelengths available:1064/532/355/266nm
- Conduction cooling, compact design
- Low plug-in power consumption, strong environmental adaptability
- Wide-temperature operation products are available for customization

Applications

Spectrum analysis

Biomedicine

Laser manufacturing

Radar ranging

Scientific research

Technical Specifications

| Optical Parameters | | | | | | |
|------------------------------------|------------------------------|----------------|---------------------|-----|-----|--|
| Wavelength (nm) | | 1064 | 532 | 355 | 266 | |
| Repetition rate (Hz) | | 1~20 | | | | |
| Pulse energy (mJ) | | 50 | 25 | 15 | 5 | |
| Pulse width (ns) | | ≤6 | | | | |
| Power stabilty (RMS) | | ≤3% | | | | |
| Full angle divergence typ. (mrad) | Horizontal @1/e ² | ≤4 | | | | |
| | Vertical @1/e² | ≤4 | | | | |
| Beam diameter (at output port, mm) | | 3*3 | | | | |
| Cooling method | | Air cooling | | | | |
| Laser dimensions (W×H×L,mm) | | 95×70 | 95×70×150 95×70×190 | | | |
| Operation temperature (°C) | | 10~35 | | | | |
| Storage temperature (°C) | | -20~60 | | | | |
| Driver Parameters | | | | | | |
| Supply power voltage | | 24VDC | | | | |
| Control interface | | J30J~21P | | | | |
| Power consumption (W) | | 120W | | | | |
| Trigger mode | | Trigger In/Out | | | | |

All the data in the above table are the typical values obtained from the tests at room temperature of $25\,\mathrm{C}$, and the final data is subject to the final test report.







Order Information


Part Numbering Schema

| Wavelength (nm) | Part Number | Repetition rate (Hz) | Pulse energy (mJ) |
|-----------------|----------------|----------------------|-------------------|
| 1064 | AQE-1064-20-50 | 20 | 50 |
| 532 | AQE-532-20-25 | 20 | 25 |
| 355 | AQE-355-20-15 | 20 | 15 |
| 266 | AQE-266-20-5 | 20 | 5 |




Mechanical Drawings (in mm)










1064nm & 532nm Drawing









355nm & 266nm Drawing

